

# UNDERLAYMENTS

## SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<b>PRODUCT NAME</b>	Modified Asphalt Roofing Membrane
<b>CHEMICAL NAME</b>	Mixture
<b>TRADE NAME</b>	<b>Roofing Underlayment</b> (Polystick TU, Polystick TU P, Polystick TU PLUS, Polystick IR-X, Polystick IR-Xe, Polystick MTS, Polystick MU, Polystick Basic, Polystick P) <b>Flooring Tile Underlayment</b> (Anti-Fracture Membrane)
<b>MANUFACTURER</b>	Polyglass USA, Inc.
<b>ADDRESS</b>	1111 West Newport Center Drive, Deerfield Beach, FL 33442
<b>PHONE</b>	(888) 410-1375
<b>INTERNET</b>	www.polyglass.com
<b>EMERGENCY PHONE</b>	800-424-9300 Chemtrec
<b>MSDS NUMBER</b>	UL01
<b>EFFECTIVE DATE</b>	December 1, 2001
<b>NFPA RATING</b>	Health 1, Reactivity 1, Flammability 0 0-least, 1-slight, 2-moderate, 3-high, 4-extreme

## SECTION 2 - PRODUCT INGREDIENT

INGREDIENT NAME	COMMON NAME	CAS number	% Weight	Exposure Limit (OSHA)	Exposure Limit (ACGIH)
Petroleum Asphalt	Asphalt	8052 42 4	38.0 - 55.2	5 mg/m3 PEL	5 mg/m3 TLV (as fume)
Calcium Carbonate	Limestone	1317 65 3	4.3 - 23.8	5 mg/m3 PEL (Respirable) 15 mg/m3 PEL (Total)	3 mg/m3 TLV (Respirable) 10 mg/m3 TLV (Total)
Polyethylene	Polyethylene	9002 88 4	0 - 1.3	5 mg/m3 PEL (Respirable) 15 mg/m3 PEL (Total)	3 mg/m3 TLV (Respirable) 10 mg/m3 TLV (Total)
Polypropylene	Polypropylene	9003 07 0	0 - 3.9	Not Established	Not Established
Ethylene Propylene Copolymer	Copolymer	9010 79 1	0 - 3.0	5 mg/m3 PEL (Respirable) 15 mg/m3 PEL (Total)	10 mg/m3 TLV (Total)
Styrene Butadiene Styrene	SBS Rubber	9003-55 8	1.8 - 7.1	Not established	Not established
Styrene Isoprene Styrene	SIS Rubber	25038 32 8	1.8 - 2.7	Not established	Not established
Polyvinyl Butyral	PVB	27360 07 2	0 - 2.0	Not established	Not established
Petroleum Hydrocarbon Resin	Resin	68527 25 3	5.0 - 7.6	Not established	Not established
Continuous Filament glass fiber	Fiberglass mat	65997 17 3	0 - 3.7	5 mg/m3 PEL (Respirable) 15 mg/m3 PEL (Total)	1 fiber/cc TLV 5 mg/m3 TLV (Total)
Crushed Mineral	Roofing granules	None assigned	0 - 28.0	Not established	Not established

## SECTION 3 - PHYSICAL/CHEMICAL DATA

PROPERTIES	UNIT	DATA
Appearance	N/A	Black roll
Boiling point	deg F	>650
Evaporation Rate	N/A	N/A
Flash Point	deg F	>430
Melting Point	deg F	>290
Odor	N/A	Mild asphalt/petroleum odor
Ph (undiluted product)	N/A	N/A
Saturation in air	%	N/A
Solids Content	N/A	N/A
Specific gravity	g/cc	1.02 - 1.30
Vapor Density Air	Air = 1	N/A
Vapor Pressure	N/A	N/A
Viscosity	cP	N/A
VOC	g/liter	N/A
Volatility	%	< 0.1
Water solubility	%	< 0.1

## SECTION 4 - FIRE AND EXPLOSION DATA

### FLAMMABILITY PROPERTIES

Flash point	>430 deg F (ASTM D92)
Lower Explosive	Limit Undetermined
Upper Explosive	Limit Undetermined

### RECOMMENDED EXTINGUISHING MEDIA

Dry chemical, foam, water fog, CO2

### UNUSUAL FIRE OR EXPLOSION HAZARDS

Burning will produce black smoke

### SPECIAL FIRE FIGHTING PROCEDURES

Wear self contained breathing apparatus

## SECTION 5 - HAZARD IDENTIFICATION

### ACUTE HEALTH EFFECTS

Irritation of eye, nose, throat, and skin

### CHRONIC HEALTH EFFECTS

Insufficient evidence of cancer induced by exposure to asphalt fumes. The International Agency for Research on Cancer (IARC) considered Crystalline Silica as a human carcinogen. Prolonged exposure to Crystalline Silica containing dust can lead to Silicosis. Continuous filament glass fibers are not classified as Carcinogens. However no significant health hazards are likely to occur due to the product form and nature of use.

Upper respiratory system

### MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED

Pre-existing respiratory conditions

### SIGNS/SYMPTOMS OF OVEREXPOSURE

Inhalation	Headache, nausea, coughing, irritation of the upper respiratory system
Skin Contact	Burns caused by contact with hot material
Skin absorption	Not applicable
Ingestion	Not intended to be ingested
Eye Contact	Irritation/redness may occur

## SECTION 6 - FIRST AID PROCEDURES

### INHALATION

Remove affected person to fresh air

### SKIN CONTACT

Rinse with cool water

### SKIN ABSORPTION

Not applicable

### INGESTION

Do not induce vomiting. Treat symptomatically.

### EYE CONTACT

Flush with copious quantities of water. Consult a physician if irritation persists.

## SECTION 7 - STABILITY/REACTIVITY DATA

### SUMMARY

Material is stable. Hazardous polymerization will not occur.

### CHEMICAL INCOMPATIBILITIES

Strong oxidizing agents, strong acids and alkalines.

### CONDITION TO AVOID

Strong oxidizing agents at elevated temperatures and uncontrolled fumes.

### THERMAL STABILITY

Stable

## SECTION 8 - HANDLING, USE AND DISPOSAL

### PROCEDURES FOR SPILLS/LEAKS

Not applicable

### WASTE DISPOSAL METHOD

Standard refuse disposal. Wastes are classified as non-hazardous by U. S. Environmental Protection Agency (EPA) and as per definition by Resource Conservation and Recovery Act (RCRA). Follow all local, state, and federal regulations governing waste disposal.

Use protective equipment as described in Section IX. Keep away from heat or flame and protect from the elements.

### HYGIENIC PRACTICE

Wash after any skin contact.

## SECTION 9 - EXPOSURE CONTROL/PERSONAL PROTECTION

### EYE

Wear safety glasses with side shields.

### SKIN

Wear leather or cotton gloves (impervious)

### VENTILATION

Although normal conditions of product use does not warrant any special ventilation, use in well ventilated area.

### RESPIRATORY

None required unless used with hot asphalt. Use breathing apparatus (only NIOSH approved) when PEL/TLV is exceeded.

### OTHER PRACTICES

None

## SECTION 10 - TRANSPORTATION

<b>Shipping</b>	name Not regulated as a hazardous material for transport
<b>Labeling</b>	Not applicable
<b>Labeling Required</b>	None required
<b>Hazard Class</b>	Not applicable

## SECTION 11 - MISCELLANEOUS INFORMATION

### COMMENTS

Sand is applied as an anti-sticking agent to the membrane. Calcium carbonate is used as a compound stabilizer and is encased in the asphaltic matrix. Fibrous glass filaments are encapsulated in modified asphalt coating. Due to the nature of the specific use of these products, hazardous exposures are highly unlikely; however all relevant data has been provided for reference.

### ADDITIONAL INFORMATION

Contact Polyglass USA at (775) 575 6007

### MSDS REVISION SUMMARY

Revision Date	December 1, 2001
Reason for Change	New format

### DISCLAIMER

Information was obtained from sources, which we believe are reliable. However the information is provided without any representation or warranty, express or implied, regarding the accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of the product.