

**MATERIAL SAFETY DATA SHEET**

NPCA

**FOR COATINGS, RESINS AND RELATED MATERIALS**  
(Approved by US Department of Labor Essentially Similar to Form OSHA 20)

<b>Date Issued</b> 4/13/07
----------------------------

**SECTION I**

## MANUFACTURERS NAME

APOC

## STREET ADDRESS

4161 E 7<sup>TH</sup> AVENUE

## CITY, STATE, AND ZIP CODE

TAMPA, FL 33605

**EMERGENCY TELEPHONE NUMBER**

1-800-424-9300

## PRODUCT CLASS

ASPHALT CLAY BASED EMULSION COATING

## MANUFACTURER'S CODE

IDENTIFICATION

APOC 337,

## TRADE NAME

APOC

**SECTION II- HAZARDOUS INGREDIENTS**

INGREDIENT	PERCENT	TLV PPM	TLV Mg/M3
PETROLEUM ASPHALT CAS # - 8052-42-4	<45%		5 As Fume
CLAY STABILIZER CAS #- 1332-58-7	<10%		2*
WATER CAS # - 7732-18-5	>50%	**	
LATEX POLYMER CAS # Mixture	10-15%	**	**

ADDITIONAL INFORMATION-\*AS RESPIRABLE FRACTION OF DUST, \*\*NOT ESTABLISHED.

**Hazardous Materials Identification System (HMIS)**

**Health**  
1

**Flammability**  
0

**Reactivity**  
0

**Personal Protection**  
B

**SECTION III – PHYSICAL DATA**BOILING RANGE: 200°F - 220°F VAPOR DENSITY  HEAVIER  LIGHTER, THAN AIREVAPORATION RATE  FASTER  SLOWER, THAN  
ETHER PERCENT VOLATILE BY VOLUME <45 % WEIGHT PER GALLON  
8.5 LBS**SECTION IV – FIRE AND EXPLOSION HAZARD DATA**

DOT CATEGORY - Not Regulated

FLASH POINT- N/A

EXTINGUISHING MEDIA- CO2, DRY CHEMICAL

UNUSUAL FIRE AND EXPLOSION HAZARDS- NONE

SPECIAL FIRE FIGHTING PROCEDURES-WEAR SELF CONTAINED BREATHING APPARATUS. WATER MAY BE USED TO COOL CLOSED CONTAINERS.

---

---

## SECTION V – REACTIVITY DATA

---

STABILITY:  UNSTABLE       STABLE      CONDITIONS TO AVOID: HEAT, FLAMES,

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON OXIDES

HAZARDOUS POLYMERIZATION:  MAY OCCUR       WILL NOT OCCUR

---

## SECTION VI-HEALTH HAZARD DATA

---

U.S. FEDERAL REGULATIONS: THIS PRODUCT HAS NOT BEEN CLASSIFIED A CARCINOGEN BY THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA), THE NATIONAL TOXICOLOGY PROGRAM (NTP) OR THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC).

EFFECTS OF OVEREXPOSURE-ACUTE: SKIN: PROLONGED /REPEATED CONTACT MAY CAUSE IRRITATION. - EYES: MAY CAUSE SLIGHT IRRITATION. -INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA.

**CALIF. PROP. 65\* CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE # 25249.5 ET SEQ)** DETECTABLE AMOUNTS OF SOME CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM MAY BE FOUND IN VARIOUS GARDNER ASPHALT CORPORATION (GARDNER) PETROLEUM BASED PRODUCTS AND THEIR VAPORS. READ AND FOLLOW LABEL DIRECTIONS AND INFORMATION GIVEN ON MATERIAL SAFETY DATA SHEETS AND USE CARE WHEN HANDLING OR USING ALL PETROLEUM PRODUCTS. EMERGENCY FIRST AID PROCEDURE-SKIN: REMOVE CONTAMINATED CLOTHING. WASH EXPOSED AREA. WITH SOAP AND WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. KEEP PERSON WARM AND QUIET. GET MEDICAL ATTENTION.

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS TIGHTLY CLOSED.

---

## SECTION VII – SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ELIMINATE SOURCES OF IGNITION KEEP PRODUCT OUT OF SEWERS BY DIKING OR IMPOUNDING. SOAK UP SPILL WITH SAND OR OTHER ABSORBENT. PLACE IN CONTAINERS. WASH AREA.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

---

## SECTION VIII – SPECIAL PROTECTION INFORMATION

---

RESPIRATORY PROTECTION: USE NIOSH/MSHA APPROVED RESPIRATOR WHEN TLV IS EXCEEDED.

VENTILATION: N/A

PROTECTIVE GLOVES: N/A

EYE PROTECTION: NOT REQUIRED

OTHER PROTECTIVE EQUIPMENT: N/A

---

## SECTION IX – REGULATORY INFORMATION

---

ALL INGREDIENTS IN THIS PRODUCT ARE TSCA LISTED.

THERE ARE NO CHEMICALS IN THIS PRODUCT REGULATED BY SARA 313, CERCLA OR TSCA12 (b).

