

Hazardous Materials Identification System (HMIS)

Health 1 Flammability 0 Reactivity 0 Personal Protection G

MSDS
MATERIAL SAFETY DATA SHEETS**#505**
Puddle Plaster™**1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION****STYRENE ACRYLIC CO-POLYMER ELASTOMERIC EMULSION****PRODUCT CODE: E*LAS*TEK #505 PUDDLE PLASTER™****MSDS DATE:** 04/18/2006**COMPANY IDENTIFICATION**Structural Elastomeric Products, Inc.
3700 S. Palo Verde Road
Tucson, Arizona 85713**EMERGENCY TELEPHONE NUMBERS**Health Emergency: 877-352-7835
Spill Emergency: 877-352-7835**2. HAZARDOUS INGREDIENTS****Hazardous**

Component	CAS %	OSHA PEL	AGG/HTLV
Asphalt	0052-42-4	Not Est.	Not Est.
Clay	1302-78-9	5mg/M ³	5mg/M ³
Cellulose Fibers	9004-34-6	5mg/M ³	5mg/M ³
Vermiculite ¹	318-00-9	Not Est	3mg/M ³

3. HAZARDS IDENTIFICATION**PRIMARY ROUTES OF EXPOSURE**Inhalation
Skin Contact
Eye Contact
Ingestion**INHALATION**

Prolonged inhalation of vapor or mist can cause the following:

Coughing, shortness of breath, dizziness, intoxication

EYE CONTACT

Material can cause the following:

Moderate irritation-burning sensation, tearing, redness, swelling

SKIN CONTACT

Prolonged or repeated skin contact can cause the following:

Dermatitis, allergic reactions

INGESTION

May be health hazard when ingested in large quantities

*NOTES TO PHYSICIAN: There is no specific antidote. Treatment of overexposure should be directed at the control of the symptoms and clinical condition.***4. FIRST AID MEASURES****INHALATION**

Remove from vapor immediately. If overcome, call a physician. If breathing has stopped or irregular, start resuscitation or administer oxygen as needed. Get prompt medical attention.

EYE CONTACT

Flush eyes with a large amount of water for at least 15 minutes. Consult a physician if irritation persists.

SKIN CONTACT

Wash skin thoroughly with soap and water. If drenched, remove and wash clothing before reuse.

INGESTION

Do not induce vomiting. Contact physician immediately.

CARCINOGENICITY: NOT PROVEN IN HUMANS**IABC MONOGRAPHS: VOLUME 15, PART 4 (1.85)****OSHA REGULATED? No****5. FIRE-FIGHTING MEASURES**Flash Point..... Noncombustible
Auto-ignition Temperature Not Applicable
Lower Explosive Limit..... Not Applicable
Upper Explosive Limit Not Applicable
Hazardous Polymerization..... Will Not Occur**EXTINGUISHING AGENTS**Foam, CO₂, Dry Chemical, Water, Fog**PERSONAL PROTECTIVE EQUIPMENT**

Firefighters should wear masks when extinguishing fires involving dried film.

SPECIAL PROCEDURES

Use water spray to cool containers exposed to fire.

6. ACCIDENTAL RELEASE MEASURES**PERSONAL PROTECTION**

Appropriate protective equipment must be worn when handling a spill of this material.

PROCEDURES

Keep spectators away. Recover free liquid. Floor may be slippery; use care to avoid falling. Contain spills immediately with an absorbent (e.g. sand, earth). Open all windows. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding, or advise authorities immediately.

CAUTION: Keep spills and runoff out of municipal sewers and open bodies of water.**7. HANDLING & STORAGE****STORAGE CONDITIONS**

Keep from freezing; material may coagulate. Do not store this material near food, feed, or drinking water.

Keep containers closed when not in use. Do not handle or store near heat or strong oxidants. Keep from freezing. Adequate ventilation required. Do not handle or store near heat or strong oxidants.

HANDLING PROCEDURES

Avoid breathing vapors. Avoid prolonged or repeated contact with skin. Remove contaminated clothing and laundry before reuse. Remove contaminated shoes and thoroughly dry before reuse. Wash skin thoroughly with soap and water after contact.

WASTE DISPOSAL METHOD

Assure conformity with applicable disposal regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION

None required if good ventilation is maintained. Otherwise, wear a MSHA/NIOSH approved (or equivalent) half-mask, air-purifying respirator when concentrated vapors are encountered.

Ventilation: Local Exhaust, Face Velocity 60 fpm

EYE PROTECTION

Use splash goggles or face shield when eye contact may occur, e.g., when spraying

HAND PROTECTION

Use chemically resistant gloves to avoid repeated or prolonged skin contact.

Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough.

ENGINEERING CONTROLS (VENTILATION)

Exterior-use product. Use local exhaust ventilation with a minimum capture velocity of 100 ft/min. (0.5 m/sec) at the point of vapor evolution.

OTHER PROTECTIVE EQUIPMENT

Use chemical resistant apron or other clothing to avoid repeated or prolonged skin contact. Remove dried residue with waterless hand cleaner; follow with soap and water.

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance	Black paste
Color	Black/Brownish
State	Paste
Odor Characteristic	Woody
Viscosity	Paste
Specific Gravity (Water = 1)	1.08
Vapor Density (Air = 1)	Heavier
Vapor Pressure	N/A
Melting Point	Variable
Boiling Point	212°F
Solubility in Water	Disperses but not soluble in water
Percent Volatility	45% Maximum
Evaporation Rate (BAc = 1)	Slower
Incompatibility	Strong Oxidants

See Section 5, Fire Fighting Measures

10. STABILITY & REACTIVITY

INSTABILITY

This material is considered stable.

HAZARDOUS POLYMERIZATION

Product will not undergo polymerization.

The information provided in this MSDS is correct to the best of our knowledge, information, and belief at the date of publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not considered a warranty or quality specification. The information relates only to the specific materials designated and may not be valid for such materials used in combination or with other materials or in any process, unless specified in the text.